

Instructions

- 1. Read the IAQ
 Backgrounder and
 the Background
 Information for
 this checklist.
- 2. Keep the
 Background
 Information and
 make a copy of
 this checklist for
 each ventilation
 unit in your school,
 as well as a
 copy for future
 reference.
- 3. Complete the Checklist.
 - Check the "yes," "no," or "not applicable" box beside each item. (A "no" response requires further attention.)
 - Make comments in the "Notes" section as necessary.
- Return the checklist portion of this document to the IAQ Coordinator.

Ventilation Checklist

School: Thomas Hooker Elementary School

David Hour

Name:

1.	OUTDOOR AIR INTAKES	
1a.	Marked locations of all outdoor air intakes on a small floor plan (for example, a fire escape floor plan))
1b.	Ensured that the ventilation system was on and operating in "occupied" mode)
AC	TIVITY 1: OBSTRUCTIONS	
lc.	Ensured that outdoor air intakes are clear of obstructions, debris, clogs, or covers	i
1d.	Installed corrective devices as necessary (e.g., if snowdrifts or leaves frequently block an intake)	ì
AC	TIVITY 2: POLLUTANT SOURCES	
le.	Checked ground-level intakes for pollutant sources (dumpsters, loading docks, and bus-idling areas)	ĺ
lf.	Checked rooftop intakes for pollutant sources (plumbing vents; kitchen, toilet, or laboratory exhaust fans; puddles; and mist from air-conditioning cooling towers)	
1g.	air-conditioning cooling towers)	ļ
A C	TIVITY 3: AIRFLOW	
1h.	Obtained chemical smoke (or a small piece of tissue paper or light plastic)	
2.	SYSTEM CLEANLINESS	
	TIVITY 4: AIR FILTERS	
	Replaced filters per maintenance schedule	
	blowing downstream)	100
	Vacuumed filter areas before installing new filters	į
	around) the air filter	É
2e.	Confirmed proper installation of filters (correct direction for airflow)	
	only room 15 has em oper sable air handling unit.	

2. SYSTEM CLEANLINESS (continued)			
ACTIVITY 5: DRAIN PANS			
2f. Ensured that drain pans slant toward the drain (to prevent water from accumulating)	No □	N/A	
2g. Cleaned drain pans		D/	
2h. Checked drain pans for mold and mildew			
ACTIVITY 6: COILS			
2i. Ensured that heating and cooling coils are clean			
ACTIVITY 7: AIR-HANDLING UNITS, UNIT VENTILATORS			
2j. Ensured that the interior of air-handling unit(s) or unit ventilator (air-mixing chamber and fan blades) is clean		П	
2k. Ensured that ducts are clean	٥	_	
ACTIVITY 8: MECHANICAL ROOMS			
21. Checked mechanical room for unsanitary conditions, leaks, and spills			
2m. Ensured that mechanical rooms and air-mixing chambers are free of trash,			
chemical products, and supplies		u	
3. CONTROLS FOR OUTDOOR AIR SUPPLY			
3a. Ensured that air dampers are at least partially open (minimum position)		·	
3b. Ensured that minimum position provides adequate outdoor air for occupants		D	
Tot occupants	_	8 55 1	
ACTIVITY 9: CONTROLS INFORMATION			
3c. Obtained and reviewed all design inside/outside temperature and humidity requirements, controls specifications, as-built mechanical drawings,			
and controls operations manuals (often uniquely designed)	¥		
ACTIVITY 10: CLOCKS, TIMERS, SWITCHES			
3d. Turned summer-winter switches to the correct position			9
3e. Set time clocks appropriately			
3f. Ensured that settings fit the actual schedule of building use (including night/weekend use)			
ACTIVITY 11: CONTROL COMPONENTS			
3g. Ensured appropriate system pressure by testing line pressure at both the occupied (day) setting and the unoccupied (night) setting			
3h. Checked that the line dryer prevents moisture buildup			
3i. Replaced control system filters at the compressor inlet based on the			
compressor manufacturer's recommendation (for example, when you blow down the tank)			
3j. Set the line pressure at each thermostat and damper actuator at the proper	1	3	S.J. thermostatoonle
level (no leakage or obstructions)			RJ. thermostation of item controled by preunatics
ACTIVITY 12: OUTDOOR AIR DAMPERS		_	Preuniaties
3k. Ensured that the outdoor air damper is visible for inspection			
31. Ensured that the recirculating relief and/or exhaust dampers are visible	П	0	
for inspection	J		
outdoor air damper is within the normal operating range			
NOTE: It is necessary to ensure that the damper is operating properly and within the range to continue.	norm	ıal	2 of 5
07 201111111111111			

2). media conter + room 15 are the only units with heating + cooking



3.	CONTROLS FOR OUTDOOR AIR SUPPLY (continued)				
3n.	Checked that the outdoor air damper fully closes within a few minutes of shutting off appropriate air handler		No	N/A	
30	Checked that the outdoor air damper opens (at least partially with no delay)		_	-	
50.	when the air handler is turned on				
3p.	If in heating mode, checked that the outdoor air damper goes to its				
	minimum position (without completely closing) when the room				
2	thermostat is set to 85°F				
3q.	If in cooling mode, checked that the outdoor air damper goes to its minimu position (without completely closing) when the room thermostat is set	m			
	to 60°F and mixed air thermostat is set to 45°F				
3r.	If the outdoor air damper does not move, confirmed the following items:				
	• The damper actuator links to the damper shaft, and any linkage set				
	screws or bolts are tight				
	Moving parts are free of impediments (e.g., rust, corrosion)				
	• Electrical wire or pneumatic tubing connects to the damper actuator	🗖			
	• The outside air thermostat(s) is functioning properly (e.g., in the right			b /	
	location, calibrated correctly)				
Pro	ceed to Activities 13 – 16 if the damper seems to be operating properly.				
	TIVITY 13: FREEZE STATS				
3s.	Disconnected power to controls (for automatic reset only) to test continuity				
ΩD	across terminals		ч	9	
OR					
3t.	red) trips the freeze stat (clicking sound indicates freeze stat was				
	tripped)	🗖		9	
3u.	Assessed the feasibility of replacing all manual reset freeze-stats with				
	automatic reset freeze-stats	🗖			
NO	TE: HVAC systems with water coils need protection from the cold. The freezo	z-stat	may		
clos	re the outdoor air damper and disconnect the supply air when tripped. The t	ypica	l trip	•	
ran	ge is 35°F to 42°F.				
AC	TIVITY 14: MIXED AIR THERMOSTATS				
3v.	Ensured that the mixed air stat for heating mode is set no higher				
	than 65°F			U	
3w.	Ensured that the mixed air stat for cooling mode is set no lower				
	than the room thermostat setting	🖵	J	<u>u</u>	
AC	TIVITY 15: ECONOMIZERS				
	Confirmed proper economizer settings based on design specifications or			/	
	local practices				
NO:	TE: The dry-bulb is typically set at 65°F or lower.				
	Checked that sensor on the economizer is shielded from direct sunlight			b	
	Ensured that dampers operate properly (for outside air, return air,			_	
J.L.	exhaust/relief air, and recirculated air), per the design specifications	🗖			
NO			no		
NOTE: Economizers use varying amounts of cool outdoor air to assist with the cooling load of the room or rooms. There are two types of economizers, dry-bulb and enthalpy.					
Dry-bulb economizers vary the amount of outdoor air based on outdoor temperature,					
	enthalpy economizers vary the amount of outdoor air based on outdoor ten				
	humidity level				

3.	CONTROLS FOR OUTDOOR AIR SUPPLY (continued)	
	TIVITY 16: FANS Ensured that all fans (supply fans and associated return or relief fans) that move outside air indoors continuously operate during occupied hours (even when room thermostat is satisfied)	1
	TE: If fan shuts off when the thermostat is satisfied, adjust control cycle as necessary to ure sufficient outdoor air supply.	
4.	AIR DISTRIBUTION	
AC	TIVITY 17: AIR DISTRIBUTION	
	Ensured that supply and return air pathways in the existing ventilation system perform as required	
4b.	Ensured that passive gravity relief ventilation systems and transfer grilles between rooms and corridors are functioning	
	TE: If ventilation system is closed or blocked to meet current fire codes, consult with a fessional engineer for remedies.	
	Made sure every occupied space has supply of outdoor air (mechanical system or operable windows)	
4d.	Ensured that supply and return vents are open and unblocked	
	TE: If outlets have been blocked intentionally to correct drafts or discomfort, investigate correct the cause of the discomfort and reopen the vents.	
4e.	Modified the HVAC system to supply outside air to areas without an outdoor air supply	
	Modified existing HVAC systems to incorporate any room or zone layout and population changes	
4g.	Moved all barriers (for example, room dividers, large free-standing blackboards or displays, bookshelves) that could block movement of air in the room, especially those blocking air yents.	
4h.	air in the room, especially those blocking air vents	
4i.	Ensured that classrooms are free of uncomfortable drafts produced by air from supply terminals	
AC	TIVITY 18: PRESSURIZATION IN BUILDINGS	
mai	TE: To prevent infiltration of outdoor pollutants, the ventilation system is designed to intain positive pressurization in the building. Therefore, ensure that the system, including exhaust fans, is operating on the "occupied" cycle when doing this activity.	
4j.	Ensured that air flows out of the building (using chemical smoke) through windows, doors, or other cracks and holes in exterior wall (for example, floor joints, pipe openings)	
5 . l	EXHAUST SYSTEMS	
AC	TIVITY 19: EXHAUST FAN OPERATION	
5a.	Checked (using chemical smoke) that air flows into exhaust fan grille(s)	
If fa	 ins are running but air is not flowing toward the exhaust intake, check for the following: Inoperable dampers Obstructed, leaky, or disconnected ductwork Undersized or improperly installed fan 	

· Broken fan belt

4 J. No chemical suske was used, a tissue was used verity

direction of airflow



5. EXHAUST SYSTEMS (continued)

ACTIVITY 20: EXHAUST AIRFLOW

NOTE: Prevent migration of inc and labs by keeping them under	door contaminants from areas such as bathrooms, kilche r negative pressure (as compared to surrounding spaces,	ns,).
5b. Checked (using chemical s adjacent spaces	moke) that air is drawn into the room from Yes N	o N/A
the door opening (see "How to	e door slightly open while checking airflow high and low Measure Airflow").	in
5c. Ensured that air is flowing t	toward the exhaust intake	ם נ
ACTIVITY 21: EXHAUST D 5d. Checked that the exhaust d under positive pressure) is	CUCTWORK Stream of the exhaust fan (which is sealed and in good condition	ם נ
6. QUANTITY OF OUT	DOOR AIR	
ACTIVITY 22: OUTDOOR	AIR MEASUREMENTS AND CALCULATIONS	
NOTE: Refer to "How to Meas	ure Airflow" for techniques.	
6a. Measured the quantity of c	outdoor air supplied (22a) to each ventilation	o 💅
6b. Calculated the number of o	occupants served (22b) by the ventilation unit	a / o
6c. Divided outdoor air supply	(22a) by the number of occupants (22b) to nntity of outdoor air supply per person (22c)	
ACTIVITY 23: ACCEPTAB	LE LEVELS OF OUTDOOR AIR QUANTITIES	
6d. Compared the existing out levels in Table 1	door air per person (22c) to the recommended	20
quantities of outdoor air to	rentilation units that supplied inadequate of ensure that outdoor air quantities (22c) meet of Table 1	0

NOTES

56. tissue was used in place of smoke

